

Stellar® Mid Size OTR Tire Service Trucks

138-15 OTR



The 138-15 Mid Size OTR is the service truck of choice when the Mini OTR is not quite large enough. The body comes in either a 15-foot flatbed or with a 15-foot rack body with over 60 cubic feet of storage for a combination OTR, fleet and AG service vehicle. The 6000 series crane will handle up to and including the 45/65x45 OTR tire. This package provides 8,500 pounds of payload. The 15-foot rack body will hold approximately forty (40) large truck tires.

The standard driver side rail folds down, for ease and safety of loading and unloading of tires, as well as sign boards for identification.

All of the underbody tool compartments come standard with the exclusive Stellar slide top doors for unobstructive storage access. Stainless steel automotive style slam latches and hardware are standard on all tool compartments.

The left front storage compartment houses the 3/8" and 1/2" hose reels, along with the FLR (filter, lubricator and regulator)

Service Body Features

- 15-foot long body
- Heavy duty steel construction
- The rack body has 46" high racks (left side folds down)
- Six (6) underbody tool compartments
- Slide top doors on all tool compartments
- Recessed, skirt-mounted halogen floodlights
- Entire body is undercoated

Crane Features

- Fully proportional radio remote control
- Fully enclosed extension boom cylinder
- Hexagon-shaped secondary and extension
- Integral-mounted pump and PTO
- Load-holding counterbalance valves



Our People. Our Products.

Specifications

Specifications

Crane Rating:	3200 Crane 32,000 ft-lbs. (4.42 t-m)
Lifting Capacities:	5,000 lbs. (2,268 kg) in close 2,200 lbs. (998 kg) at full extension
Controls:	Proportional Radio Control
Stowed Height:	68.50 inches (173.99 cm)
Mounting Space Req:	24 inches (60.96 cm)
Shipping Weight:	1,900 lbs. (862 kg)



Specifications

Crane Rating:	4500 Crane 45,000 ft-lbs. (6.22 t-m)
Lifting Capacities:	7,500 lbs. (3,402 kg) in close 3,200 lbs. (1,452 kg) at full extension
Controls:	Proportional Radio Control
Stowed Height:	72 inches (182.88 cm)
Mounting Space Req:	26 inches (66.04 cm)
Shipping Weight:	2,400 lbs. (1,089 kg)



Specifications

Crane Rating:	6000 Crane 60,000 ft-lbs. (8.29 t-m)
Lifting Capacities:	10,000 lbs. (4,536 kg) in close 4,250 lbs. (1,927 kg) at full extension
Controls:	Proportional Radio Control
Stowed Height:	77 inches (195.58 cm)
Mounting Space Req:	32 inches (81.28 cm)
Shipping Weight:	3,150 lbs. (1,429 kg)



The 138-15 Mid Size OTR truck can be equipped with either a model 3200, 4500 or 6000 hydraulic knuckleboom crane.

These cranes are designed to handle the largest of farm tires and the smaller sized OTR tires. These cranes are both operated by a standard fully proportional radio remote control. Capacity specifications are found on the back of this brochure. Accessories include, 1/2" x 50' and 3/8" x 50' hose reels, optional 12V trouble light, plastic storage bins and socket racks.

The SHD-66DD direct-driven hydraulic-drive air compressor is mounted on the crane base. This compressor has a 46 CFM at 175 PSI output. The location allows for cool, clean, fresh air intake, and easy maintenance and serviceability.



Our People. Our Products.

190 State Street
P.O. Box 169
Garner, IA 50438

Telephone: (641) 923-3741 • (800) 321-3741

Fax: (641) 923-2812

Internet: www.stellarindustries.com

Email: sales@stellarindustries.com

All specifications are subject to change without notification.
For the most up to date version of this brochure, please visit www.stellarindustries.com.

Copyright © 2013 Stellar Industries, Inc.

4/13