

# Stellar® Large OTR Tire Service Trucks

# 9000 AG OTR



**The Stellar 9000 AG OTR series, features a rugged, heavy-duty 15' steel OTR service body with over 60 cubic feet of storage.**

The 9000 AG OTR is equipped with a model 9000 hydraulic knuckleboom crane. This crane is operated by a standard fully proportional radio remote control. The hexagon shaped secondary and extension boom greatly increase boom strength over competitive square-shaped booms, ensuring solid performance.

The tire sizes the 9,000 lb. crane can lift include the 36.00-51 mounted narrow base and 50/65-51 wide base tires (crane only). The performance of the 9000 OTR series can be enhanced by the addition of the TM4110 Tire Manipulator.

The TM4110 allows versatility while providing a safe method to handle a variety of OTR tires up to 110 inch diameter, or 4,600 lbs. It also offers 140° of articulation and 240° of body rotation giving the TM4119 the ability to service fleets with small to medium sized OTR tires.

#### **Service Body Features**

- Heavy duty steel construction
- Flatbody has eight (8) D-ring tie downs
- Stainless steel rotary slam latches
- Slide top doors on all tool compartments
- Recessed, skirt-mounted halogen floodlights
- Rubber mounted running lights
- Entire body is undercoated
- Calcium pump system with 400-gallon reinforced polypropylene tank and air operated fluid mixer

#### **Crane Features**

- Rotation is accomplished through a turnable bearing
- Fully proportional radio remote control
- Fully enclosed extension boom cylinder
- Hexagon-shaped secondary and extension
- Integral-mounted pump and PTO on chassis
- Load-holding counterbalance valves



*Our People. Our Products.*

# Specifications

## Specifications

Crane Rating: 90,000 ft-lbs (12.45 t-m)  
Standard Boom Length: 12' 11" (3.93 m)  
Boom Extension: Hydraulic 37" (93.98 cm)  
Max. Horizontal Reach: 16 ft (4.88 m)  
Max. Vertical Lift: 22 ft (6.71 m)  
Rotation: 290 degree power (hourglass worm gear)

Lifting Capacities: 9,000 lbs. @ 10 ft (4,082 kg @ 3.05 m)  
6,950 lbs. @ 12 ft - 11 in (3,152 kg @ 3.93 m)  
5,625 lbs. @ 16 ft (2,551 kg @ 4.88 m)

Power Supply Req: PTO & Pump (Fully Proportional VB)  
12 gpm @ 3000 psi  
(45.4 lpm @ 206 bars)

Controls: Fully proportional radio remote standard,  
with manual controls on valve bank

Stowed Height: 84 in (213.36 cm)  
Mounting Space Req: 42 in (107 cm)  
Shipping Weight: 4,800 lbs. (2,175 kg)

## Specifications

Tireman Capacity: 4,600 lbs (2,087 kg)  
Clamping Span:  
• Fixed Pads 48" to 110" (122 cm to 279 cm)  
• Cylinder Rotating Pads 47" to 109" (119 cm to 277 cm)

Optional Pad Extension: 29" (73.66 cm) - arms closed  
Clamp Cylinders: 2.50" (6.35 cm) w/ pilot operated check valve  
Tilt Cylinder: Provided by crane extension boom  
Body Rotation: 285-degree power  
Rotation System: Rotation bearing & worm driven gear box  
Clamping Pad Rotation: None – Stationary Pads  
Tilt: +85 degrees to -37 degrees  
Hydraulic Controls: Incorporated with the crane controls  
Shipping Weight: 1,550 lbs (703 kg)

## Compressor

SHD-66DD direct driven, mounted above deck for maintenance ease  
4-cylinder, 2-stage, capable of 46 CFM @ 175 PSI



Shown with optional rack side body with vertical compartments for more storage and fold down rack.

All specifications are subject to change without notification.  
For the most up to date version of this brochure, please visit [www.stellarindustries.com](http://www.stellarindustries.com).

Copyright © 2016 Stellar Industries, Inc.  
4/16



Our People. Our Products.

190 State Street  
P.O. Box 169  
Garner, IA 50438  
Telephone: (641) 923-3741 • (800) 321-3741  
Fax: (641) 923-2812  
Internet: [www.stellarindustries.com](http://www.stellarindustries.com)  
Email: [sales@stellarindustries.com](mailto:sales@stellarindustries.com)