

# SUPER CHARGER

## HYDRAULIC PRESSURE INTENSIFIER



### Specifications

- Will operate with a minimum of 6 gpm or a maximum of 40 gpm of hydraulic flow
- Will operate with a minimum of 2500 PSI to a maximum of 4500 PSI working pressure
- Pressure and flow self-regulate
- Will operate on 12 or 24 volt system
- Equipped with 12 or 24 volt thermostatic-controlled heat element to maintain warm hydraulic oil
- All models standard with adjustable flow to tool
- In-line filter on return line from tool to supply tank

Connecting directly into crane's hydraulic system, it has a 4-gallon of hydraulic oil supply dedicated for tools and will eliminate the agony of air line freeze up and the hassle of trying to keep extra air pots warm by rotating in and out of the heated cab in order to complete a job.

This unit will produce 10,000 PSI of hydraulic working pressure for hydraulic jacks and rams. Connecting directly into crane's hydraulic system, it has a 4-gallon of hydraulic oil supply dedicated for tools.

Control of the Super Charger is done through a programmable remote for single or double functions, that includes a manual override.

\*Specifications may change without notification.

Your Contact:

Telephone: 800-392-3015  
E-mail: [sales@americaneagleacc.com](mailto:sales@americaneagleacc.com)  
[www.americaneagleacc.com](http://www.americaneagleacc.com)

Designed & Manufactured in the U.S.A.  
Copyright © 2016 American Eagle Accessories Group