



 CONTINUAL ABILITY TO HANDLE

 OCCASIONAL ABILITY TO HANDLE

 INABILITY TO HANDLE

# OTR Tire Capacity Chart

OTR Tire Size	Tire Width	Weight	3200	4500	6000	9000 (Carrier Only)	4,600# TM4110 9000	6,000# TM6116 13500	7,200# TM7120 17000	12,000# TM12154 23000	16,500# TM16160 28000	TM20165
<b>Narrow Base</b>		<b>Tire &amp; Rim</b>										
18.00 – 25	66 in.	1,100 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
18.00 – 33	74 in.	1,650 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
21.00 – 35	82 in.	2,050 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
24.00 – 35	87 in.	2,400 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
24.00 – 49	101 in.	3,400 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
27.00 – 49	107 in.	4,600 lb.	Red	Green	Green	Green	Yellow	Green	Green	Green	Green	Green
30.00 – 51	115 in.	5,900 lb.	Red	Yellow	Green	Green	Red	Yellow	Green	Green	Green	Green
33.00 – 51	122 in.	6,700 lb.	Red	Red	Yellow	Green	Red	Red	Green	Green	Green	Green
36.00 – 51	129 in.	8,300 lb.	Red	Red	Red	Green	Red	Red	Red	Green	Green	Green
37.00 R57	136 in.	10,000 lb.	Red	Red	Red	Red	Red	Red	Red	Green	Green	Green
40.00 – 57	143 in.	11,500 lb.	Red	Red	Red	Red	Red	Red	Red	Yellow	Green	Green
48/95 R57	151 in.	12,400 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
50/90 R57	151 in.	12,700 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
53/80 R63	149 in.	14,000 - 17,000 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Yellow	Green
55/80 R63	153 in.	16,400 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Yellow	Green
59/80 R63	154 in.	18,500 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Yellow	Green





 CONTINUAL ABILITY TO HANDLE

 OCCASIONAL ABILITY TO HANDLE

 INABILITY TO HANDLE

# OTR Tire Capacity Chart

OTR Tire Size	Tire Width	Weight	3200	4500	6000	9000 (Carrier Only)	4,600# TM4110 9000	6,000# TM6116 13500	7,200# TM7120 17000	12,000# TM12154 23000	16,500# TM16160 28000	TM20165
<b>Narrow Base</b>		<b>Tire &amp; Rim</b>										
23.5 – 25	66 in.	1,500 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
26.5 – 25	71 in.	2,000 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
29.5 – 29	75 in.	2,500 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
33.25 – 29	83 in.	1,600 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
35/65 -33	81 in.	2,900 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
33.25 – 35	91 in.	3,400 lb.	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
37.25 – 35	95 in.	4,000 lb.	Yellow	Green	Green	Green	Green	Green	Green	Green	Green	Green
40/65 – 39	94 in.	4,200 lb.	Yellow	Green	Green	Green	Yellow	Green	Green	Green	Green	Green
37.5 – 39	100 in.	4,300 lb.	Yellow	Green	Green	Green	Yellow	Green	Green	Green	Green	Green
45/65 – 45	108 in.	6,300 lb.	Red	Yellow	Green	Green	Red	Red	Green	Green	Green	Green
37.5 – 51	113 in.	4,900 lb.	Red	Green	Green	Green	Red	Green	Green	Green	Green	Green
50/65 -51	121 in.	8,000 lb.	Red	Red	Red	Green	Red	Red	Red	Green	Green	Green
67.5/65 – 51	138 in.	13,000 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
50/80 – 57	144 in.	11,000 lb.	Red	Red	Red	Red	Red	Red	Red	Yellow	Green	Green
55.5/80 – 57	147 in.	13,000 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
49.5/85 – 57	154 in.	12,900 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
55/85 R57	147 in.	12,900 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
53.5/85 – 57	154 in.	13,600 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
58/85 – 57	156 in.	13,000 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green
70/70 – 57	160 in.	15,400 lb.	Red	Red	Red	Red	Red	Red	Red	Red	Green	Green

