

CRANE COMPARISON CHART - UPDATED DECEMBER 2023

	CRANE MODEL	MAX LIFT* Lbs	MAX REACH		WINCH LINE SPEED*** Ft/Min	LENGTH OF WIRE ROPE Ft	MAX FT-LB		POWER SUPPLY	EXTENSION		RADIO CONTROL		CRANE WEIGHT Lbs
			Vertical	Horizontal**			Std	Boost		Hydraulic	Manual	On/Off	Proportional	
ELECTRIC	EC2000	2,000	10'9"	7'	20	40'	6,500		Elec		1	x		230 - 300
	EC3200 Aluminum	3,200	16'2"	15'	15	65'	11,500		Elec	1	1	x		500
	EC3200	3,200	16'2"	15'	15	65'	11,500		Elec	1	1	x		730
	EC4000-16	4,000	17'4"	16'	15	90'	16,000		Elec	1	1	x		970
	EC4000-20	4,000	21'3"	20'	15	90'	16,000		Elec	1	1	x		1,180
	EC5000	5,000	21'3"	20'	16	90'	25,000		Elec	1	1	x		1,180
	EC6000	6,000	22'10"	21'	16	90'	38,000		Elec	1	1	x		1,600
T-BOOM	TC13 - 2	2,400	11'6"	8'10"	30	65'	8,600		Elec or Hyd	2			CDT™	420 - 560
	TC23 - 2	3,970	13'4"	11'	30	65'	16,635		Elec or Hyd	2			CDT™	580 - 720
	TC23 - 3	3,745	16'6"	14'	30	65'	16,635		Elec or Hyd	3			CDT™	660 - 800
	TC33 - 2	4,865	16'5"	12'4"	30	65'	23,350		Elec or Hyd	2			CDT™	800 - 940
	TC33 - 3	4,580	19'8"	16'	30	65'	23,350		Elec or Hyd	3			CDT™	930 - 1,070
	TC38	4,940	22'11"	19'8"	30	65'	26,660		Elec or Hyd	4			CDT™	1,010 - 1,150
HYDRAULIC	3315	3,200	17'8"	15'	30	65'	11,500		Elec or Hyd	1 or 2	1 or 0	x	CDT™	770 - 940
	4421	4,000	22'7"	21'	25	90'	16,000		Elec or Hyd	1 or 2	1 or 0	x	CDT™	905 - 1,090
	5521	5,000	22'11"	21'	70	90'	25,000	29,500	Elec or Hyd	1 or 2	1 or 0		CDT™	1,275 - 1,480
	6521	6,000	22'11"	21'	70	90'	30,000	35,000	Elec or Hyd	1 or 2	1 or 0		CDT™	1,275 - 1,480
	NEW 7621	7,500	22'11"	21'	60	100'	38,000	44,840	Hyd	2			CDTpro™	1,560
	NEW 7630	7,500	31'6"	29'8"	60	120'	38,000	44,840	Hyd	2			CDTpro™	1,715
	NEW 8621	8,600	22'11"	21'	60	100'	45,000	53,100	Hyd	2			CDTpro™	1,580
	NEW 8630	8,600	31'6"	29'9"	60	120'	45,000	53,100	Hyd	2			CDTpro™	1,735
	NEW 9621	9,000	23'1"	21'	60	100'	60,000	70,800	Hyd	2			CDTpro™	2,025
	NEW 9630	9,000	31'9"	29'9"	60	120'	60,000	70,800	Hyd	2			CDTpro™	2,250
	NEW 10621	10,000	23'	21'	60	100'	60,000	70,800	Hyd	2			CDTpro™	2,025
	NEW 10630	10,000	31'9"	29'9"	60	120'	60,000	70,800	Hyd	2			CDTpro™	2,250
	NEW 12621	12,000	23'1"	21'	55	100'	66,000	77,800	Hyd	2			CDTpro™	2,025
	NEW 12630	12,000	31'9"	29'9"	55	120'	66,000	77,800	Hyd	2			CDTpro™	2,250
NEW 14530	14,000	31'11"	29'11"	60	120'	78,000	92,000	Hyd	2			CDTpro™	2,850	



* Double part line; divide by 2 for single part line
 ** From center line of base
 *** Winch speed shown at single part line

Stellar® CDT™ and Stellar® CDTpro™ are trademarks of Stellar Industries, Inc.
 *Information is subject to change without notice